

	Model	SF-565P
General	Size (WxDxH)	14.3 x 15.7 x 12.1 inches
	Weight	21.4 lbs
	LCD	2 lines x 16 chars
	Interface	USB 1.1 (compatible with USB 2.0), IEEE 1284 Parallel
	OS	Windows 95/98/Me/NT4.0/2000/XP, Various Linux OS (via
	Compatibility	USB interface only) including RedHat, Caldera, Mandrake,
	*	Slackware, SuSE, and TurboLinux.
		USB 1.1 (compatible with USB 2.0), IEEE 1284 Parallel
	Warm-up Time	Less than 35 seconds (from sleep mode)
	Noise **	Warm up: Less than 52 dBA Stand by: Less than 39 dBA Printing: Less than 52 dBA
	Power Requirement	100 ~ 127 VAC, 50/60 Hz, 4.0A 220 ~ 240 VAC, 50/60 Hz, 2.5A
	Power Consumption	Sleep mode: 10W (100~127 VAC)/12W (220~240 VAC) Standby mode: 85W (100~127 VAC)/95W (220~240 VAC) Average: 300W
	Operating Conditions	Temperature: 10-32 celsius (50~89 F)
	Duty Cycle, Monthly	Up to 10,000 pages
	Print	Method
Speed ***		Up to 16ppm in A4 (17 ppm in Letter)
Resolution		Up to 600x600 dpi
FPOT (First Print Out Time)		Approx 12 secs (from Standby mode)
Emulation		SPL (Samsung Printer Language)
Memory		4 MB (4 MB Max)
Duplex Print		Manual
Copy		Speed ****
	Resolution (optical)	Up to 200 x 200 dpi
	Resolution (Enhanced)	Up to 300 x 300 dpi
	First Copy Out Time	Approx. 30 secs (from Standby mode)
	Zoom Rate	50~150%
	Multy Copy	1~99 pgs
	Duplex Copy	-
Scan	Compatibility	Twain standard
	Method	Mono CIS
	Resolution (Optical)	Up to 200 x 200 dpi
	Resolution (Enhanced)	Up to 1200 x 1200 dpi

	Effective	15.7 inches
	Scan Length	
	Effective	8.2 inches
	Scan Width	
	Color Bit	-
	Depth	
	B/W Bit	1 bit for Text mode, 8 bit for Gray mode
	depth	
	Gray Scale	256 levels
Fax	Compatibility	ITU-T Group 3, ECM
	Applicable	Public Switched Telephone Network (PSTN) or behind PABX line
	Modem	33.6 Kbps
	Speed	
	Modem	33600/28880/21600/19200/14400/12000/9600/7200/4800/2400
	Speeds	bps with fall back
	Transmission	Approx. 3 secs per page
	Speed *****	
	Compression	MH / MR / MMR (ECM mode)
	Mode	
	Scan Speed	Approx 6 secs per page

	Resolution	Max: Up to 203 x 392 dpi Standard: Up to 203 x 98 dpi Fine: Up to 203 x 196 dpi Super Fine: Up to 203 x 392 dpi Photo: Up to 203 x 196 dpi
	Memory	2MB (Approx. 160 pgs at ITU-T #1 Chart)
	Auto Dial	1-touch dial: 20 locations Speed dial: 80 locations
	Battery	Max 92 hours
	Backup	
	Color Fax	Yes (send only)
	RX Duplex	Yes
	Print Out	
Paper	Input	250-sheet Cassette Tray, 1-sheet Manual Tray
Handling	Capacity,	
	Types	
	Output	150-sheet face down, 1 sheet face up
	Capacity,	
	Types	
	Media Sizes	Tray: Letter, A4, Legal, Folio, A5, A6 Manual Tray: Letter, Legal, A4, Folio, Executive, A5, A6, A6 Card, Post Card 4x6, Hagaki, Envelope 7-3/4, Envelope 9, Envelope 10, Envelope DL, Envelope C5, Envelope C6, Envelope B5 76 x 127 mm (3" x 5") ~ 216 x 356 mm (8.5" x 14")
	(for print)	
	Media Sizes	Letter, A4, Legal
	(for	
	fax/copy)	
	Media Types	Tray : Plain Paper Manual Tray : Plain Paper, Transparency

	ADF	20 sheets
	Capacity	
Consumables	Type	Single Cartridge
	Yield	Approx 3,000 pages at IDC @ 5% coverage.
	Toner Code	SCX-4216D3
Options		Ethernet 10/100 Base TX (External)